

PRODUCT INFORMATION

MUDD THE FINISHER

DESCRIPTION

MUDD THE FINISHER SILICONE SEALANT is an ideal sealant for jointing tiled walls and floors in interior and exterior locations as well as gap filling and sealing around showers, baths, sinks and worktops. Do not use for aquariums.

Available in a range of colours to match MUDD GROUT WITH CLOUT

This product is available in 12x310ml.

APPLICATION

- 1. Ensure all joints are clean, dry and free from soap or grease.
- 2. Remove nozzle and cut off tip of the cartridge, leaving the thread intact. Screw on nozzle and cut at 45°, to give width of seal required.
- 3. Apply a steady bead of silicone using a sealant/caulking gun to the area required.
- 4. Smooth the silicone using a wetted spatula. The sealant skins in 10 minutes at 4mm depth and will be fully cured in 24 hours. Any excess can be removed with a trimming knife.
- 5. Once opened contents can remain usable for up to 3 months providing the nozzle is sealed with the end-cap.

NOTE

Not suitable for use in aquariums.

MUDD THE FINISHER must not be used on sensitive surfaces e.g. marble, which may react with the acetic acids released during curing.

COVERAGE

12.5m x 5mm x 5mm bead approx.

STORAGE & SHELF LIFE

12 months in normal dry conditions. Store between 5° and 25°C.

Please refer to the Material Safety Data Sheet for further information on health and safety issues.

TECHNICAL ADVISORY SERVICE

For free expert guidance on the use of this product or any aspect of ceramic tiling telephone the TECHNICAL ADVISORY SERVICE on: Tel: 01782 591120 Fax: 01782 591121.

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract tort, or otherwise) whatsoever for any loss, damage, or expense arising from the misuse of any information it supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or update information from time to time.